METMINCO

Towards a mid-tier copper producer



29 May 2014



Disclaimer

This presentation (the "Presentation") is strictly confidential to the recipient and has been prepared by Metminco Limited ("Metminco" or the "Company") based on the information available to it. It is intended solely for the information of the initial recipient of this presentation. Metminco is not under any obligation to update or keep current the information contained herein.

Each recipient of this Presentation is deemed to have agreed to accept the qualifications, limitations and disclaimers set out below. To the maximum extent permitted by law, none of Metminco and its related entities or their respective members, directors, officers, employees, advisors or representatives nor any other person makes any representation or gives any warranty, express or implied, as to the accuracy, reliability or completeness of the information contained in this Presentation including any forecast or prospective information. To the maximum extend permitted by law, no responsibility for any errors or omissions and no liability for any loss howsoever arising from any use of this Presentation whether arising out of negligence or otherwise is accepted by Metminco and its related entities, or their respective members, directors, officers, employees, advisors or representatives nor any other person.

This Presentation may not be reproduced, retransmitted or distributed to the press or any other person or published, in whole or in part, for any purpose.

Although all reasonable care has been undertaken to ensure that the facts stated and opinions given in this Presentation are accurate, the information provided in this Presentation has not been independently verified.

Any forward looking information in this Presentation has been prepared on the basis of a number of assumptions, subjective judgments and analyses which may prove to be incorrect. There are a number of factors that could cause results or events to differ from current expectations. Actual future events may vary materially from the forward looking information on which those statements are based. Although the Company has attempted to take into account important factors that could cause actual costs or results to differ materially, there may be other factors that cause costs of the Company's activities or results not to be as anticipated, estimated or intended. This Presentation should not be relied upon as a recommendation or forecast by the Company. Metminco disclaims any intention or obligation to update or revise any forward looking statements, whether as a result of new information, future events or otherwise.

This Presentation and the information contained in it does not constitute a prospectus, admission document or product disclosure statement (including for the purpose of the Corporations Act 2001) relating to the Company and has not been approved by the UK Listing Authority or the Australian Securities Exchange. This Presentation has not been approved by or lodged with the Australian Securities and Investment Commission.

The information in this document is provided for informational purposes only and is subject to change without notice. This Presentation does not constitute or form part of any offer for sale or solicitation of any offer to buy or subscribe for any securities nor shall it or any part of it form the basis of or be relied on in connection with, or act as any inducement to enter into, any contract or commitment whatsoever or constitute an invitation or inducement to engage in investment activity.





- > Portfolio of mineral assets in top two copper producing countries Peru and Chile
 - Los Calatos, Peru long life, low cost copper-molybdenum project
 - Porphyry hosted: 1.42Bt at 0.47% Cu & 0.022% Mo (0.15% & 0.35% CuEq cut-off)
 - Open pit and underground (block cave) mining operation
 - Conventional sulphide flotation
 - Mollacas, Chile low cost SX-EW copper project with potential for early cash flow
 - Oxide and supergene: 15.5Mt at 0.51% CuT (0.2% Cu cut-off)
 - Open pit operation
 - Heap leach, solvent extraction/electrowinning
 - Vallecillo, Chile advanced polymetallic exploration project
 - Breccia hosted: 8.9Mt at 0.80g/t Au, 9.94g/t Ag, 1.01% Zn & 0.32% Pb (0.2g/t Au cutoff)
 - Additional resources to be delineated
 - Potential open pit operation with gravity and conventional sulphide flotation



Located in prolific Cu – Mo mining district

Close proximity to substantial open pit mining operations

| AREQUI | | | Unit | Cuajone | Toquepala | Cerro Verde |
|---|--------------------------------------|--------------|---------------------------------------|---------|-----------|-------------|
| A | Cerro Verde mine | Δ | Started production | 1976 | 1960 | 1976 |
| | Chapi mine 🛠 MOQUEGUA | 1 | Reserves: ¹ Cu grade | 0.50% | 0.37% | 0.38% |
| No. | | | Mo grade | 0.018% | 0.017% | 0.013% |
| Tia Mara project | Quellaveco project Toquepala mine | | Cut-off grade (CuEq) | 0.14% | 0.16% | 0.17% |
| Metminco projectMajor towns | Smelter | · · | Strip ratio | 4.37 | 7.67 | 0.76 |
| Major roads Roads | Smelter Refinery | CT- | 2012 Cu production (kt) | 159 | 152 | 270 |
| Railway lines Southern Copper facilities | SPCC port | ~ <u>i</u> (| Open Pit Depth (m) | ±800 | ±825 | |
| Southern Copper rail line | Pacific Ocean TACNA | * / * | Net Unit Cost (C1) \$/lb ² | 1.08 | 1.72 | 1.31 |
| 0 | 100km | | | | | |

¹ As at December 2012; ² BMO Equity Research 2012



Los Calatos in brief

| 100% owned, large undeveloped Cu-Mo project | Measured, Indicated and Inferred Mineral Resource of 1.42Bt at 0.47% Cu & 0.022% Mo (6.7Mt Cu metal) |
|---|---|
| Located in prolific Cu- Mo mining district of Southern Peru | Nearest neighbours include the Toquepala, Cuajone and Cerro Verde mining operations and the Quellaveco project |
| Project of National Interest | Right to acquire surface rights/freehold directly from the Peruvian government for development (12,700ha) |
| Comprehensive exploration program | Total of 125,000m of drilling completed (135 drill holes) |
| Scoping Study | Mining Scoping Study by NCL confirms Los Calatos as potential long life, low cost, copper mine |
| Optimisation of production schedule | Optimisation work by RPM confirms opportunity to increase production rate C1 Cash Operating Costs US\$1.12/Ib Cu (net of by-product credits) |



Regional infrastructure

- Road and Access
 - Close to Pan American highway (50km) and the Port of Ilo (100km SW)

Proposed Services Corridor



- Power likely to be sourced from the regional city of Moquegua 32km SSE of the project
- Power costs low

Services Corridor

 Services corridor to be established to the coast – pumping of sea water to site and of concentrate to a port loading facility

Water

- Sea water to be accessed for metallurgical processing
- Small reverse osmosis plant
- Freehold Site Infrastructure
 - Land to be purchased from government



Source: Google Earth



Simplified geology and Cu and Mo isograde lines (1900m RL)



Key Facts

- Supergene mineralisation in upper 250m
- Near surface high-grade Cu
 & Mo domains in northwest
- Mineralisation largely located in porphyry & adjacent wall rock
- Mineralisation extends to depths in excess of 1,500m
- Younger diatreme complex partly mineralised (margins)
- Porphyry developed in favourable structural setting relating to the Incapuquio Fault System



Geological sections – distribution of Cu mineralisation





Mineral Resource Statement – February '13

Mineral Resources to vertical depth of 700 metres below surface (above 2300 masl)

| Category | Tonnes (millions) | Cu % | Мо % |
|----------------------------|-------------------|------|-------|
| Measured | 222 | 0.37 | 0.031 |
| Indicated | 191 | 0.38 | 0.020 |
| Total Measured & Indicated | 413 | 0.37 | 0.026 |
| Inferred | 80 | 0.42 | 0.009 |

Note: Reported at a cut-off grade of 0.15% CuEq

Mineral Resources sub-700 metres below surface (below 2300 masl)

| Category | Tonnes (millions) | Cu % | Мо % |
|----------------------------|-------------------|------|-------|
| Measured | 206 | 0.49 | 0.032 |
| Indicated | 437 | 0.52 | 0.020 |
| Total Measured & Indicated | 643 | 0.51 | 0.024 |
| Inferred | 283 | 0.52 | 0.018 |

Note: Reported at a cut-off grade of 0.35% CuEq

Total contained copper

7.8 million tonnes CuEq metal

Note: CuEq based on Cu = 2.75/lb and Mo = 15.00/lb



Optimised L3_Model – RPM (August 2013)



Mining infrastructure

Open pit

- Strip ratio of 3.36:1
- Pit slopes 41° to 47°

Underground block cave

- 3 Levels
- 10 bulk mining stopes
- Twin decline system for ore conveyor system and personnel & materials
- Four raise-bored ventilation shafts
- Primary crusher located underground



Optimised L3_Model - Annual tonnage & CuEq grade





Optimised L3_Model - Tonnes mined and grade

Optimised L3_ Model - Total Tonnes Mined (RPM – August 2013)

| Mining Operation | Tonnes (million) | Cu % | Мо % |
|--------------------------|------------------|------|-------|
| Open Pit | 362 | 0.37 | 0.023 |
| Underground – Block Cave | 449 | 0.56 | 0.035 |
| Total | 811 | 0.47 | 0.029 |

Total metal mined

• 3.85 million tonnes Cu & 0.24 million tonnes Mo



Key operating parameters – Life of Mine

Combined Open Pit & Underground Operational Parameters

| Devementer | Life of Mine | | |
|--|--------------------|--|--|
| Parameter | Optimised L3_Model | | |
| Total tonnes mined (million) | 811 | | |
| Average annual tonnes mined (million) | 23.9 | | |
| Average annual copper in concentrate (kt) | 98.4 | | |
| Average annual molybdenum in concentrate (kt) | 4.8 | | |
| Strip Ratio (Open Pit) | 3.36:1 | | |
| Mining costs (US\$/t tonnes milled) | 7.72 | | |
| Processing costs (US\$/t tonnes milled) | 4.58 | | |
| G & A costs (US\$/t tonnes milled) | 0.51 | | |
| By-product credit (US\$/lb payable copper) | 0.73 | | |
| Cash Operating Costs net of credits (US\$/lb Cu) | 1.12 | | |
| Pre-production capital (US\$ million) | 1,320 | | |

Low C1 Cash Operating Costs • US\$1.12/Ib Cu places project in lowest quartile of producers



Current work

- Preparatory work for pre-feasibility study includes:
 - Design of infill drilling program
 - ✓ Supergene zone
 - ✓ Geotechnical
 - ✓ Sterilisation
 - Geotechnical work in support of planned open pit and underground block cave operations
 - Phase 2 metallurgical test work
 - ✓ Use of seawater as a processing medium
 - Location of site infrastructure (e.g. tailings dam)
 - Positioning of access corridor to the coast
 - Oceanographic studies loading facility
- Commencement of pre-feasibility study dependent on funding



Chilean Projects

Chilean projects located to east of La Serena





Mollacas in brief 100% owned, small undeveloped Copper Measured and Indicated Mineral Resource of 15.5Mt @ 0.51%CuT Leach project Located in close • Close to the town of Rapel with road infrastructure and access to power and proximity to water infrastructure Comprehensive • Total of 16,280m of drilling completed (119 drill holes) exploration program Comprehensive Phase 3 test work results support higher copper recoveries and lower acid metallurgical test work consumption completed • Scoping Study completed by SRK (2008) updated to include latest **Scoping Study** metallurgical test work results, and revised Opex and Capex estimates • Life of Mine of >7 years producing up to 8,000t copper cathode per annum **Robust financials** • After tax NPV @ 8% of US\$75 million (Cu price = US\$3.10/lb)



Mollacas Copper Leach Project

- Located 55km ESE of Ovalle
- Project area comprises 33km² of tenements
- Includes 20 Exploitation Concessions
- > 179ha of surface rights held
- Water rights held to ±175 litres/sec from two canals





Legal - Access

First Extension to Initial Servidumbre/Easement declared invalid



Mollacas target – supergene cap of primary porphyry

Secondary Sulphide Zone – highest copper grades (50 - 100m below surface)





Copper leach project – Mineral Resource Estimate

Mineral Resource Estimate – Oxide & Secondary Sulphide Zone (July 2012)

| Cotoroni | | Grade | | Contained Metal | | | |
|-----------|-------------|---------|------------|-----------------|---------|------------|---------|
| Category | Tonnes (Mt) | CuT (%) | Cu_Sol (%) | Au (g/t) | CuT (t) | Cu_Sol (t) | Au (oz) |
| Measured | 11.2 | 0.55 | 0.44 | 0.124 | 61,424 | 49,140 | 44,523 |
| Indicated | 4.3 | 0.41 | 0.29 | 0.138 | 17,687 | 12,510 | 19,140 |
| Total | 15.5 | 0.51 | 0.40 | 0.128 | 79,111 | 61,650 | 63,663 |

Note: Reported at a 0.20% CuT cut-off grade

Note: Rounding-off of figures may result in minor computational discrepancies

| Data support : July 2012 Resource | • 95 diamond drill holes (12,784m) and 24 reverse circulation drill holes (3,496m) |
|--------------------------------------|--|
| | |
| Mineral Resource | Fully converted to Measured and Indicated categories |
| | |
| Low grade primary porphyry | Transitional and primary resource of 18.8Mt at 0.28% CuT and 0.187g/t Au |



Mollacas progressing towards development

Completed

- Updated Scoping study
- Resource definition drilling
- Geotechnical design work for open pit & leach pads
- Phase 3 column leach test work
- Preliminary layout of mining infrastructure
- Environmental baseline study
- Provisional LoM Financial Model

Planned

- Feasibility Study (end-2014)
- Environmental Impact Study (end-2014)

Preliminary layout – SX/EW operation





Phase 3 metallurgical test work yields positive results



Checking the flow rates at the top of the 6 metre columns, SGS laboratory, Santiago, Chile.

- Two Stage Leach
 - 90 day Primary Leach at 5L/hm² at 6 g/L H₂SO₄
 - 210 day Secondary Leach at 2.5 L/hm² at 3 g/L H₂SO₄
- Solution management via a series/parallel SX configuration

Metallurgical testing

- 16 columns representing 5 geometallurgical units
- Acid consumption in agglomeration stage reduced from 30kg/t to 10kg/t ore leached
- > 85% soluble copper
- > Ore crush size of P80 12mm to 16mm
- Stacked ore depth of 6 metres
- Opportunity to reduce acid consumption in agglomeration stage further



Life of mine financial model yields robust results

| Physicals | Unit | Parameter |
|---|--------------------|-------------------|
| Mining rate | tpd | 6,108 |
| Crushing rate | ktpa | 2,500 |
| Tonnes leached | kt | 14,500 |
| Average Cu_Sol | % | 0.42% |
| Payable Cu | t | 51,765 |
| LoM | Years | 7 |
| Financials | Unit | Parameter |
| Total Capital Expenditure | US\$000's | 52,306 |
| | | |
| C1 Cash Operating Costs | US\$/lb Cu | 1.23 |
| C1 Cash Operating Costs Project Economics | US\$/lb Cu Unit | 1.23 Parameter |
| | | |
| Project Economics | Unit | Parameter |



Status

Corporate

- Cash-on-hand as at 31 March 2014 of A\$5.5m
- In Situ mining inventory of 3.9 million tonnes (8.5 billion lbs) contained copper to be mined over 34 years

Los Calatos

- Highly deliverable with designated status of 'Project of National Interest'
- Optimisation Study (August 2013) identifies project as potential long life, low cost, copper producer
- Funding requirements necessitate the introduction of a funding partner
- Ability to transact impacted by low market capitalisation of Company undervalues the project

Mollacas

- Robust financial returns
- First Easement Extension declared invalid which impacts on access
- Awaiting results of appeal lodged with the Supreme Court of Chile
- Securing social licence imperative
- Feasibility Study and EIS to be completed once access is resolved

> Way Forward

- Restructuring has provided for funding to early FY2015
- Growth opportunities beyond existing asset base being assessed
- Funding options for the medium term currently under consideration

